



4850 ?

CST C829 - 22x11-8 TL 2PR 10.5-13.5 P.S.I. 4 35-160 LBS 4.5-9.5

22*11-8

CST C829

22*11-8 TL 2PR 10.5-13.5 P.S.I. 4 35-160 LBS 4.5-9.5

22*11-8 CST C829 ? 22*11-8 TL 2PR 10.5-13.5 P.S.I. 4 35-160 LBS 4.5-9.5

CST C829	Size	TL	P.R.	Load Capacity (kg)	P.S.I.	Load Capacity (LBS)	Inflation	Speed
						?? / LBS		
	145/70-6	TL	2	5.5	4	35 / 75	4.5	2.0
	16*8-7	TL	2	10	4	58 / 125	6.5	3.0
	20*7-8	TL	2	8.5	4	71 / 157	5.5	
	21*9-8	TL	2	12	4	125 / 275	7.0	
	18*9.50-8	TL	2	10	4	80 / 175	7.0	
	22*11-8	TL	2	11	4	125 / 275	9.0	
	25*12-9	TL	2	13	4	160 / 355	9.5	

PR - 2PR (2 Ply)

TL - Tubeless

[22*11-8 TL 2PR 10.5-13.5 P.S.I. 4 35-160 LBS 4.5-9.5](#)

22*11-8 TL 2PR 10.5-13.5 P.S.I. 4 35-160 LBS 4.5-9.5

0