



5090 ?

CST C829 - 22*11-8 P.R. 2 TL 5.5 4 125/275 9.0
 22*11-8 P.R. 2 TL 10 4 125/275 9.0
 22*11-8 P.R. 2 TL 11 4 125/275 9.0
 22*11-8 P.R. 2 TL 13 4 160/355 9.5

CST C829

CST C829

22*11-8 P.R. 2 TL 5.5 4 125/275 9.0
 22*11-8 P.R. 2 TL 10 4 125/275 9.0
 22*11-8 P.R. 2 TL 11 4 125/275 9.0
 22*11-8 P.R. 2 TL 13 4 160/355 9.5

22*11-8 CST C829 P.R. 2 TL 5.5 4 125/275 9.0

CST C829	Size	P.R.	TL	P.S.I	Load Capacity (LBS)	Speed Rating	Tread Depth (mm)
16*8-7	2	TL	4	58 / 125	6.5	3.0	
20*7-8	2	TL	4	71 / 157	5.5		
21*9-8	2	TL	4	125 / 275	7.0		
18*9.50-8	2	TL	4	80 / 175	7.0		
22*11-8	2	TL	4	125 / 275	9.0		
25*12-9	2	TL	4	160 / 355	9.5		

PR - P.R. (P.R.)

TL - TL (Tubeless)

[22*11-8 CST C829 P.R. 2 TL 5.5 4 125/275 9.0](#)

22*11-8 CST C829 P.R. 2 TL 5.5 4 125/275 9.0

_____0